Aberhof.



TECHNICAL DATA	VALUE
Brand	ABERHOF
Collection	CARMELITA
Country of production	CHINA
Thickness	5 mm
Transparency thickness	0.55 mm
Weight	8.452 kg/m ²
Additional protective varnish	yes
Size of the plank/tile	61,5 x 12,3 cm
Relief / coating surface Structure	synchronous/standard
Chamfer	4∨
Connection type	lock
Quantity per pack	2.421 ²
Fire hazard class (Russia)	КМ5
Fire-technical characteristics: Flammability (B)	B3
Fire performance characteristics: smoke developed (Д)	ДЗ
Fire-technical characteristics: toxicity (T)	Τ4
Fire-technical characteristics: flame propagation (PП)	РП4
Resistance to furniture legs on the roller	average
Noise reduction	18 dB
Absolute residual deformation	<0,1 mm
Antistatic properties	<2 kV
Service life, years	20
Price range	=CC28 rub/=CC19 rub/=CC20 rub/=CC21 rub/=CC22 rub/=CC23 rub/=CC25 rub/=CC27
The approximate level of retail prices is determined by the results of selective monitoring.	rub/=CC26 rub/=CC24 rub
Tile Туре	SPC



Direct link to the collection at bigfloor.pro

Aberhof.



LVT / SPC ABERHOF / CARMELITA Current assortment of colors



0058

1682



0420



0532



0701





1862



2593



2594



2599



Images of designs may differ from actual product samples due to the color rendition of the printing industry.