

TECHNICAL DATA	VALUE
Brand	NOVENTIS
Collection	ASGARD
Country of production	RUSSIA
Thickness	4 mm
Transparency thickness	0.3 mm
Weight	7.78 kg/m ²
Additional protective varnish	yes
Size of the plank/tile	60,0 x 30,0 cm
Relief / coating surface Structure	standard
Chamfer	4V
Connection type	lock
Quantity per pack	1.8 ²
Fire hazard class (Russia)	KM2
Fire-technical characteristics: Flammability (B)	B2
Fire performance characteristics: smoke developed (Д)	Д2
Fire-technical characteristics: toxicity (T)	T2
Fire-technical characteristics: flame propagation (ПП)	ПП1
Resistance to furniture legs on the roller	average
Noise reduction	3 dB
Absolute residual deformation	<0,1 mm
Antistatic properties	<2 kV
Service life, years	20
Price range	=CC71 rub/=CC72 rub/=CC69 rub/=CC70 rub
The approximate level of retail prices is determined by the results of selective monitoring.	
Tile Type	SPC




Direct link
to the collection at bigfloor.pro


LVT / SPC
NOVENTIS / ASGARD
Current assortment of colors




Kari 5003



Skadi 5004



Freyya 5000



KHolda 5001

Images of designs may differ from actual product samples due to the color rendition of the printing industry.