TECHNICAL DATA	VALUE
Brand	NOVENTIS
Collection	ASGARD
Country of production	RUSSIA
Overall thickness	4 mm
Thickness of the protective layer	0.3 mm
Weight	7.78 kg/m^2
Additional protective varnish	yes
Size of the plank/tile	60,0 x 30,0 cm
Relief / coating surface Structure	standard
Chamfer	4V
Connection type	lock
Quantity per pack	1.8 m2
Fire hazard class (Russia)	KM2 / KM3 / KM4 / KM5 / KM6 / KM7 / KM8
Fire-technical characteristics: Flammability (B)	B2 / B3 / B4 / B5 / B6 / B7 / B8
Fire performance characteristics: smoke developed (Д)	Д2 / Д3 / Д4 / Д5 / Д6 / Д7 / Д8
Fire-technical characteristics: toxicity (T)	T2 / T3 / T4 / T5 / T6 / T7 / T8
Fire-technical characteristics: flame propagation (РП)	РП1 / РП2 / РП3 / РП4 / РП5 / РП6 / РП7
Resistance to furniture legs on the roller	average
Impact noise reduction index	3/4/5/6/7/8/9 dB
Absolute residual deformation	<0,1/<0,2/<0,3/<0,4/<0,5/<0,6/<0,7 mm
Service life	20 years
Antistatic properties	<2 kV
Tile Type	SPC

Direct link
to the collection at bigfloor.pro

LVT / SPC
NOVENTIS / ASGARD
Current assortment of colors



BERGEN 5010



GERI 5007



IMIR 5005



KARI 5003



MAGNI 5008



ODIN 5006



SKADI 5004



TRONKHEYM 5009



FREYYA 5000



KHOLDA 5001

Color images may differ from actual product samples due to color reproduction characteristics and screen settings.