



TECHNICAL DATA	VALUE
Brand	ABERHOF
Collection	CARMELITA GD
Country of production	CHINA
Thickness	2.5 mm
Transparency thickness	0.55 mm
Weight	5.0752519596865 kg/m²
Additional protective varnish	yes
Relief / coating surface Structure	standard
Chamfer	4V
Connection type	glue
Quantity per pack	60 ²
Fire hazard class (Russia)	KM5
Fire-technical characteristics: Flammability (B)	В3
Fire performance characteristics: smoke developed (Д)	дз
Fire-technical characteristics: toxicity (T)	Т4
Fire-technical characteristics: flame propagation (PΠ)	РП4
Resistance to furniture legs on the roller	high
Noise reduction	2 dB
Absolute residual deformation	<0,1 mm
Antistatic properties	<2 kV
Service life, years	25
Price range The approximate level of retail prices is determined by the results of selective monitoring.	=CC178 rub/=CC179 rub/=CC180 rub/=CC181 rub/=CC182 rub/=CC183 rub/=CC184 rub/=CC185 rub
Tile Type	LVT



Direct link to the collection at bigfloor.pro





LVT / SPC ABERHOF / CARMELITA GD Current assortment of colors



 $Images \ of \ designs \ may \ differ \ from \ actual \ product \ samples \ due \ to \ the \ color \ rendition \ of \ the \ printing \ industry.$