## Aberhof.

TECHNICAL DATA	VALUE
Brand	ABERHOF
Collection	CHEVRON
Country of production	CHINA
Overall thickness	5 mm
Thickness of the protective layer	0.55 mm
Weight	10.49 kg/m²
Additional protective varnish	yes
Size of the plank/tile	63,5x12,7 cm
Relief / coating surface Structure	standard
Chamfer	4V
Connection type	lock
Quantity per pack	1.7742 m <sup>2</sup>
Fire hazard class (Russia)	КМ5
Fire-technical characteristics: Flammability (B)	B3
Fire performance characteristics: smoke developed (Д)	ДЗ
Fire-technical characteristics: toxicity (T)	T4
Fire-technical characteristics: flame propagation (PII)	РП4
Resistance to furniture legs on the roller	average
Impact noise reduction index	2 dB
Absolute residual deformation	<0,1 mm
Antistatic properties	<2 kV
Service life	20 years
Tile Type	SPC



Direct link to the collection at bigfloor.pro

## Aberhof.

## LVT / SPC ABERHOF / CHEVRON Current assortment of colors



OAK ARDENNES 2197



OAK AUSTERLITZ 1600



OAK DUNKIRK 8816



OAK GETTYSBURG 2016



OAK MARENGO 2196



OAK MARNE 2195



OAK SOMMA 8810



OAK VERDUN 2165



OAK WATERLOO 1010



WALNUT AZINCOURT 8112

Images of designs may differ from actual product samples due to the color rendition of the printing industry.