

TECHNICAL DATA	VALUE
Brand	BERRYALLOC
Collection	PURELOC 40
Country of production	CHINA
Thickness	5 mm
Transparency thickness	0.4 mm
Weight	8.023 kg/m ²
Additional protective varnish	yes
Size of the plank/tile	17,7x121 cm
Relief / coating surface Structure	standard
Chamfer	4V
Connection type	lock
Quantity per pack	1.709 ²
Fire hazard class (Russia)	KM2
Fire-technical characteristics: Flammability (B)	B2
Fire performance characteristics: smoke developed (Д)	Д2
Fire-technical characteristics: toxicity (T)	T2
Fire-technical characteristics: flame propagation (ПП)	ПП1
Resistance to furniture legs on the roller	average
Noise reduction	20 dB
Absolute residual deformation	<0,1 mm
Antistatic properties	<2 kV
Service life, years	20
Price range	=CC98 rub/=CC100 rub/=CC29 rub/=CC30 rub/=CC102 rub/=CC101 rub/=CC31 rub/=CC97 rub/=CC103 rub/=CC99 rub
The approximate level of retail prices is determined by the results of selective monitoring.	
Tile Type	SPC



Direct link
to the collection at bigfloor.pro

LVT / SPC
BERRYALLOC / PURELOC 40
Current assortment of colors



AUTUMN OAK



BLIZZARD OAK




DESERT OAK



HONEY OAK



MIST OAK



NATURAL OAK



NEPAL GREY



POLAR OAK



SEA OAK



SUMMER OAK

Images of designs may differ from actual product samples due to the color rendition of the printing industry.