TECHNICAL DATA	VALUE
Brand	BERRYALLOC
Collection	SPIRIT 30 GD
Country of production	CHINA
Overall thickness	2 mm
Thickness of the protective layer	0.3 mm
Weight	3.45 kg/m^2
Additional protective varnish	yes
Size of the plank/tile	18,4 x 122 cm
Relief / coating surface Structure	standard
Chamfer	4V
Connection type	glue
Quantity per pack	3.36444 m2
Fire hazard class (Russia)	KM2
Fire-technical characteristics: Flammability (B)	B2
Fire performance characteristics: smoke developed (Д)	Д2
Fire-technical characteristics: toxicity (T)	T2
Fire-technical characteristics: flame propagation (РП)	РП1
Resistance to furniture legs on the roller	average
Impact noise reduction index	2 dB
Absolute residual deformation	<0,1 mm
Service life	15 years
Antistatic properties	<2 kV
Tile Type	LVT
Related products	Glue

Direct link
to the collection at bigfloor.pro

LVT / SPC
BERRYALLOC / SPIRIT 30 GD
Current assortment of colors



CANYON BROWN 1392



COLD RIVER 2813



COSY NATURAL 6862



FRENCH LIGHT 1332



GRACE GREIGE 1272



GRACE NATURAL 1212



LOFT NATURAL 7392



MOUNTAIN BROWN 5232



MOUNTAIN ICE 1532



PALMER NATURAL 1301

Color images may differ from actual product samples due to color reproduction characteristics and screen settings.